



FOTON

AUMARK



AUMARK
5-156-AMT HIGH SPECIFICATIONS

	AMT
Drive Style	4x2
Steering Wheel Position	Right Hand
MASS	
Manufacturer's Gross Vehicle Mass (GVM)	8,900 kg
Manufacturer's Gross Combination Mass (GCM)	14,500 kg
Manufacturer's Front Axle Mass (GA Front)	3,100 kg
Manufacturer's Rear Axle Mass (GAU Rear)	6,000 kg
Permissible Gross Vehicle Mass (V)	8,900 kg
Permissible Gross Combination Mass (D/T)	14,500 kg
Permissible Front Axle Mass (A Front)	3,100 kg
Permissible Rear Axle Mass (A Rear)	6,000 kg
Unladen Front Axle Mass (T Front)	1,740 kg
Unladen Rear Axle Mass (T Rear)	1,060 kg
Unladen Mass Total (Tare)	2,800 kg
DIMENSIONS	
Overall Length (OL)	6,930 mm
Overall Width (OW)	2,136 mm
Overall Height (OH)	2,250 mm
Front Overhang (FOH)	1,110 mm
Rear Overhang (ROH)	2,010 mm
Wheelbase (WB)	3,800 mm
Cab to End of Chassis (CE)	5,200 mm
Cab to Rear Axle (CA)	3,230 mm
Turning Radius (TR)	8.5 m
Fuel Tank Capacity (FTC)	120 Litres
PERFORMANCE	
Maximum Speed	105 km/h
Gradeability at V	30%
ENGINE	
Make	CUMMINS
Model	ISF3.8s3154
Max Power- Kw@R/Min	115/2600
Max Power-HP @ R/Min	156/2600
Max Torque-N.M @ R/Min	500/1200-1900
Cylinder	4
Capacity	3.76
TRANSMISSION	
Manufacturer	Foton Light Transmission
Model	6AU558TO
Type	6 Speed AMT
Torque	550
Speed Ratios	I:5.762 II:2.922 III:1.638 IV:1.000 V:0.782 R:5.149

CLUTCH	
Diameter	362 mm
Type	Single Plate
Operation	Diaphragm Spring
AXLE	
Front Axle	Whole I Type
Rear Axle	Punched and Welded Single-Stage Reduction Drive Axle
Rear Axle Ratio	4.30
SUSPENSION	
Front	Leaf Spring
Rear	Leaf Spring
BRAKES	
System Type	Full Air - Dual Circuit
Emergency	Spring Potential Brake
Auxiliary	Exhaust Brake
ABS	Yes
CAB	
Cab Control	Forward Tilt Cab
No. of Seats	3
ELECTRICAL SYSTEM	
System Voltage	24V
No. of Batteries	2 x 24V
TYRE	
Tyre Size	215/75R17.5-14PR
Type	Radial
WARRANTY	
Warranty	2 Year / Unlimited Mileage
KEY FEATURES	
LED Daytime Running Lights	
Remote Central Locking	
Airconditioning	
MP3 + Bluetooth + Rear Parking Radar	
Cruise Control	
Driver and Passenger Airbags	
Cummins and ZF Powertrain Support	



FOTON

AUMARK



AUMARK

5-156-AMT LOW SPECIFICATIONS

	AMT
Drive Style	4x2
Steering Wheel Position	Right Hand
MASS	
Manufacturer's Gross Vehicle Mass (GVM)	8,900 kg
Manufacturer's Gross Combination Mass (GCM)	14,500 kg
Manufacturer's Front Axle Mass (GA Front)	3,100 kg
Manufacturer's Rear Axle Mass (GAU Rear)	6,000 kg
Permissible Gross Vehicle Mass (V)	8,900 kg
Permissible Gross Combination Mass (D/T)	14,500 kg
Permissible Front Axle Mass (A Front)	3,100 kg
Permissible Rear Axle Mass (A Rear)	6,000 kg
Unladen Front Axle Mass (T Front)	1,740 kg
Unladen Rear Axle Mass (T Rear)	1,060 kg
Unladen Mass Total (Tare)	2,800 kg
DIMENSIONS	
Overall Length (OL)	6,930 mm
Overall Width (OW)	2,136 mm
Overall Height (OH)	2,250 mm
Front Overhang (FOH)	1,110 mm
Rear Overhang (ROH)	2,010 mm
Wheelbase (WB)	3,800 mm
Cab to End of Chassis (CE)	5,200 mm
Cab to Rear Axle (CA)	3,230 mm
Turning Radius (TR)	8.5 m
Fuel Tank Capacity (FTC)	120 Litres
PERFORMANCE	
Maximum Speed	105 km/h
Gradeability at V	30%
ENGINE	
Make	CUMMINS
Model	ISF3.8s3154
Max Power- Kw@R/Min	115/2600
Max Power-HP @ R/Min	156/2600
Max Torque-N.M @ R/Min	500/1200-1900
Cylinder	4
Capacity	3.76
TRANSMISSION	
Manufacturer	Foton Light Transmission
Model	6AU558TO
Type	6 Speed AMT
Torque	550
Speed Ratios	I:5.762 II:2.922 III:1.638 IV:1.000 V:0.782 R:5.149

CLUTCH	
Diameter	362 mm
Type	Single Plate
Operation	Diaphragm Spring
AXLE	
Front Axle	Whole I Type
Rear Axle	Punched and Welded Single-Stage Reduction Drive Axle
Rear Axle Ratio	4.30
SUSPENSION	
Front	Leaf Spring
Rear	Leaf Spring
BRAKES	
System Type	Full Air - Dual Circuit
Emergency	Spring Potential Brake
Auxiliary	Exhaust Brake
ABS	Yes
CAB	
Cab Control	Forward Tilt Cab
No. of Seats	3
ELECTRICAL SYSTEM	
System Voltage	24V
No. of Batteries	2 x 24V
TYRE	
Tyre Size	215/75R17.5-14PR
Type	Radial
WARRANTY	
Warranty	2 Year / Unlimited Mileage
KEY FEATURES	
LED Daytime Running Lights	
Remote Central Locking	
Airconditioning	
MP3 + Bluetooth	
Cruise Control	
Cummins and ZF Powertrain Support	